


RayOne Trifocal Technical Information







RayOne Trifocal Technical Information

Model Name	RayOne Trifocal
Model Number	RAO603F
Power Range	0.0 D to +30.0 D (increments 0.5D) Trifocal, diffractive, +3.5 D near add and +1.75 D intermediate add at the IOL plane

Delivery System	
Injector Type	Single use, fully preloaded IOL injection system
Nozzle Size	1.65 mm
Bevel Angle	45°
Lens Delivery	Single handed plunger

Aspheric Trifocal IOL			
Material	Single piece Rayacryl hydrophilic acrylic		
Water Content	26% in equilibrium		
UV Protection	Benzophenone UV absorbing agent		
UV Light Transmission	UV 10% cut-off is 380 nm		
Refractive Index	1.46		
ABBE	56		
Overall Diameter	12.50 mm		
Optic Diameter	6.00 mm		
Optic Shape	Biconvex (positive powers)		
Asphericity	Aberration-neutral technology		
Optic Edge Design	Amon-Apple 360° enhanced square edge		
Haptic Angulation	O°, uniplanar		
Haptic style	Closed loop with anti-vaulting haptic (AVH) technology		

Estimated Constants for Optical Biometry							
SRK/T	Haigis			HofferQ	Holladay		
A-constant	a0	a1	a2	pACD	SF		
118.6	1.044	0.40	0.10	5.32	1.56		

For Contact Ultrasound, the estimated A-constant is 118.0

Please note that the constants indicated for all Rayner lenses are estimates and are for guidance purposes only. Surgeons must always expect to personalise their own constants based on initial patient outcomes, with further personalisation as the number of eyes increases.

Discover why RayOne is in a class of its own visit rayner.com/rayone



Regulatory restrictions may apply in certain markets. ©Rayner 2018. RayOne is a registered mark of Rayner. EC 2018-135 09/19